


ANNIE Phase I - Status and Perspectives

New Perspectives 2016 - June 13th, 2016

Vincent Fischer

University of California, Davis



June 13th, 2016




UC DAVIS
UNIVERSITY OF CALIFORNIA

The ANNIE experiment

- **ANNIE** is the Accelerator Neutrino-Neutron Interaction Experiment
- Water Cherenkov detector placed downstream of the Booster Neutrino Beam
- Aims at measuring the production rate of neutrons from neutrino interactions in water
- Significant impact in proton decay searches and neutrino-nucleon interactions understanding





ANNIE Phase 1 - Goals



- "Proof of concept" → Measurement of the neutron background rate
- Source of neutron background:
 - Skyshine neutrons → Neutrons from the beam dump entering the detector
 - Dirt neutrons → Neutrons originating from neutrino interactions downstream of the dump
- March-May 2016: Installation in the SciBooNE hall
- Taking data since June 2016 until the 2016 Summer shutdown (end of July)
- Different detector configuration than for the Physics run

ANNIE Phase 1 - Goals



- "Proof of concept" → Measurement of the neutron background rate
- Source of neutron background:
 - **Skyshine neutrons** → Neutrons from the beam dump entering the detector
 - **Dirt neutrons** → Neutrons originating from neutrino interactions downstream of the dump
- March-May 2016: Installation in the SciBooNE hall
- Taking data since June 2016 until the 2016 Summer shutdown (end of July)
- Different detector configuration than for the Physics run

ANNIE Phase 1 - The detector



The tank

- 10x13' tank covered with a white liner for light collection
- Filled with 26-ton of ultrapure water
- Equipped with 60 8-inch photomultipliers (from SuperK, lent by UC Irvine) at the bottom



ANNIE Phase 1 - The detector



The tank

- 10x13' tank covered with a white liner for light collection
- Filled with 26-ton of ultrapure water
- Equipped with 60 8-inch photomultipliers (from SuperK, lent by UC Irvine) at the bottom

The Muon Range Detector (MRD)

- First 2 layers in use (55 channels) instead of the 10 layers (362 channels) used in SciBooNE



ANNIE Phase 1 - The detector



The tank


- 10x13' tank covered with a white liner for light collection
- Filled with 26-ton of ultrapure water
- Equipped with 60 8-inch photomultipliers (from SuperK, lent by UC Irvine) at the bottom

The Muon Range Detector (MRD)

- First 2 layers in use (55 channels) instead of the 10 layers (362 channels) used in SciBooNE
- Combined with the veto, it tags muons going through the detector



ANNIE Phase 1 - The detector



The tank

- 10x13' tank covered with a white liner for light collection
- Filled with 26-ton of ultrapure water
- Equipped with 60 8-inch photomultipliers (from SuperK, lent by UC Irvine) at the bottom

The Muon Range Detector (MRD)


- First 2 layers in use (55 channels) instead of the 10 layers (362 channels) used in SciBooNE
- Combined with the veto, it tags muons going through the detector

The Neutron Capture Volume (NCV)

- Neutron-sensitive subvolume within the tank
- 50x50 cm acrylic vessel (from UC Davis) filled with 100 liters of Gd-doped liquid scintillator
- Can be moved in the tank using a winch system


ANNIE Phase 1 - Tank installation

- Tank preparation and PMT installation done at the D0 Assembly Building
- Tank filled with 7000 gallons of ultrapure water
- Water continuously flushed with nitrogen and filtered through a de-ionizing purification system
- Water quality requirement → Resistivity $> 10 \text{ M}\Omega\cdot\text{m}^{-1}$ (0.05 ppm)
- Water commissioning →
 - Observation of muon events
 - PMT characterization using LEDs



ANNIE Phase 1 - Tank installation

- Tank preparation and PMT installation done at the D0 Assembly Building
- Tank filled with **7000 gallons** of ultrapure water
- Water continuously flushed with nitrogen and filtered through a de-ionizing purification system
- Water quality requirement →
Resistivity $> 10 \text{ M}\Omega\cdot\text{m}^{-1}$ (**0.05 ppm**)
- Water commissioning →
 - Observation of muon events
 - PMT characterization using LEDs





ANNIE Phase 1 - Tank installation

- Tank preparation and PMT installation done at the D0 Assembly Building
- Tank filled with **7000 gallons** of ultrapure water
- Water continuously flushed with nitrogen and filtered through a de-ionizing purification system
- Water quality requirement → Resistivity $> 10 \text{ M}\Omega\cdot\text{m}^{-1}$ (**0.05 ppm**)
- Water commissioning →
 - Observation of muon events
 - PMT characterization using LEDs



ANNIE Phase 1 - NCV installation



- **100 liters** of EJ-335 liquid scintillator ordered from the Eljen company

→ **Pseudocumene-based** (high light yield), **0.25% Gd-doping** (high neutron capture cross-section)

- Filling safely performed in collaboration with ES&H and the Fire Dept.
- Using the winch, the NCV can be moved in the vertical direction and along the beam direction

→ **Allows a measurement of the neutron rate at different locations within the tank**

ANNIE Phase 1 - Electronics and Data Acquisition

High voltage system


- Experts: University of Sheffield, UK
- 81 negative channels (veto, MRD) and 60 positive channels (tank PMTs)
- LabVIEW-based web interface for remote monitoring and control



ANNIE Phase 1 - Electronics and Data Acquisition

High voltage system

- Experts: University of Sheffield, UK
- 81 negative channels (veto, MRD) and 60 positive channels (tank PMTs)
- LabVIEW-based web interface for remote monitoring and control



Data acquisition system


- Experts: Iowa State University and Queen Mary University, UK
- 16 VME-based FADC cards developed at the University of Chicago for the KOTO collaboration
- Veto and each MRD layer combined using a CAMAC DAQ and sent to the trigger board



ANNIE Phase 1 - Electronics and Data Acquisition

High voltage system

- Experts: University of Sheffield, UK
- 81 negative channels (veto, MRD) and 60 positive channels (tank PMTs)
- LabVIEW-based web interface for remote monitoring and control



Data acquisition system

- Experts: Iowa State University and Queen Mary University, UK
- 16 VME-based FADC cards developed at the University of Chicago for the KOTO collaboration
- Veto and each MRD layer combined using a CAMAC DAQ and sent to the trigger board



Trigger system

- Experts: Iowa State University
- Primary mode: Beam trigger
- Possibility to use an external trigger for cosmics searches or LED calibration


ANNIE Phase 1 - Light calibration



- **Goals:**
 - Monitor the PMT response to Cerenkov and scintillation light
 - Control the light attenuation in water
 - Monitor the PMT gain in-situ and continuously


- **4 LEDs** attached to the top of the tank
 - One blue and one green LED on each side, one equipped with a teflon diffuser
 - Can be plugged in directly to a pulse generator → Very easy to use

ANNIE Phase 1 - Light calibration





- **Goals:**
 - Monitor the PMT response to Cerenkov and scintillation light
 - Control the light attenuation in water
 - Monitor the PMT gain in-situ and continuously
- **4 LEDs** attached to the top of the tank
- One blue and one green LED on each side, one equipped with a teflon diffuser
- Can be plugged in directly to a pulse generator → Very easy to use

ANNIE Phase 1 - Data analysis






- Neutron capture search: All waveforms after a beam trigger recorded for 80 μ s
- **Event definition** \rightarrow Coincidence of 5 or more PMT pulses above a certain threshold and within a given time window
- Background reduction: Comparison between cosmic muon, beam muon and neutron capture events
- Possibility to separate Cerenkov and scintillation light using pulse shape analysis

ANNIE Phase 1 - Data analysis



- Neutron capture search: All waveforms after a beam trigger recorded for 80 μ s
- **Event definition** \rightarrow Coincidence of 5 or more PMT pulses above a certain threshold and within a given time window
- Background reduction: Comparison between cosmic muon, beam muon and neutron capture events
- Possibility to separate Cerenkov and scintillation light using pulse shape analysis


ANNIE Phase 1 - Data analysis



- Neutron capture search: All waveforms after a beam trigger recorded for 80 μ s
- **Event definition** \rightarrow Coincidence of 5 or more PMT pulses above a certain threshold and within a given time window
- Background reduction: Comparison between cosmic muon, beam muon and neutron capture events
- Possibility to separate Cerenkov and scintillation light using pulse shape analysis



ANNIE Phase 1 - First data

- **First muon** observed during the water commissioning phase
- Excess of events observed in coincidence with the RWM signal from the BNB
- Neutron captures → Excess of events (exponential shape) after beam signal
- Pattern observed in the very first data taken with the NCV → Neutron captures, Michel electrons





ANNIE Phase 1 - First data

- **First muon** observed during the water commissioning phase
- Excess of events observed in coincidence with the RWM signal from the BNB
- Neutron captures → Excess of events (exponential shape) after beam signal
- Pattern observed in the very first data taken with the NCV → Neutron captures, Michel electrons





ANNIE Phase 1 - First data

- **First muon** observed during the water commissioning phase
- Excess of events observed in coincidence with the RWM signal from the BNB
- Neutron captures → Excess of events (exponential shape) after beam signal
- Pattern observed in the very first data taken with the NCV → Neutron captures, Michel electrons




ANNIE Phase 1 - First data

- **First muon** observed during the water commissioning phase
- Excess of events observed in coincidence with the RWM signal from the BNB
- Neutron captures \rightarrow Excess of events (exponential shape) after beam signal
- Pattern observed in the very first data taken with the NCV \rightarrow Neutron captures, Michel electrons




ANNIE Phase 1 - The future



- Data taking can continue even without beam → Cosmic data
- Design studies in progress to install small **LAPPDs** in the tank in a near future
- Possibility of adding **Gadolinium** to the water under investigation
- This **ANNIE 'Phase 1b'** will take place right after the Summer shutdown

ANNIE Phase 1 - The future



- Data taking can continue even without beam → Cosmic data
- Design studies in progress to install small **LAPPDs** in the tank in a near future
- Possibility of adding **Gadolinium** to the water under investigation
- This **ANNIE 'Phase 1b'** will take place right after the Summer shutdown



Conclusion

- **ANNIE Phase 1 is now complete and taking data !**
- First data looks very promising
- Huge effort undergoing on analysis
- Precise simulations of the beam (muons and neutrons generation) and the detector (response to neutron capture) are required
- A 'Phase 1b' will happen in the next fiscal year

Conclusion

- **ANNIE Phase 1 is now complete and taking data !**
- First data looks very promising
- Huge effort undergoing on analysis
- Precise simulations of the beam (muons and neutrons generation) and the detector (response to neutron capture) are required
- A 'Phase 1b' will happen in the next fiscal year

Conclusion

- **ANNIE Phase 1 is now complete and taking data !**
- First data looks very promising
- Huge effort undergoing on analysis
- Precise simulations of the beam (muons and neutrons generation) and the detector (response to neutron capture) are required
- A 'Phase 1b' will happen in the next fiscal year

Conclusion

- **ANNIE Phase 1 is now complete and taking data !**
- First data looks very promising
- Huge effort undergoing on analysis
- Precise simulations of the beam (muons and neutrons generation) and the detector (response to neutron capture) are required
- A 'Phase 1b' will happen in the next fiscal year


Conclusion

- **ANNIE Phase 1 is now complete and taking data !**
- First data looks very promising
- Huge effort undergoing on analysis
- Precise simulations of the beam (muons and neutrons generation) and the detector (response to neutron capture) are required
- A 'Phase 1b' will happen in the next fiscal year

Thank you for your attention !


Back-up

SciBooNE




- SciBar: Scintillator tracking detector (14'000 bars, 14 tons)
- Electron Catcher: 2 planes of calorimeter (lead and scintillating fibers)
- Muon Range Detector
- Measurement of CC-QE, CC- π^{\pm} , CC- π^0 , NC-ES cross-sections

Booster Neutrino Beam




- 8 GeV protons from Booster beam
- Beryllium target, reversible horn polarity
- Mean neutrino energy of 700 MeV
- Composition: 93 % of ν_μ , 6.4 % of $\bar{\nu}_\mu$ and 0.6 % of $\bar{\nu}_e$ and ν_e



Neutron capture on H/Gd


n-H capture

- Capture time: $\sim 200 \mu\text{s}$
- 2.2 MeV emitted in one gamma
- Higher accidental background (natural radioactivity)



n-Gd capture

- Capture time: $\sim 20 \mu\text{s}$ (0.25% Gd-loading)
- $\sim 8 \text{ MeV}$ emitted in several gammas
- High background reduction
- Smaller diffusion path length



Liquid scintillators

- Scintillation: Process by which ionization produced by charged particles excites a material and light is emitted by fluorescence
- Liquid scintillators: Organic molecules diluted in an optically-inert liquid (mineral oil,..)
- Basically: Charged particle ionizes liquid \rightarrow Excites molecules that de-excites emitting light
- This light is detected using photomultiplier tubes (PMT's) that amplify it into a detectable current

